

Marine Stainless 2 in 1

1. BEFORE USE:

- Shake Well.
- Ensure stainless steel surface is completely dry. (Fig. 1).

2. APPLICATION:

- Use a microfibre cloth, microfibre pad or non-abrasive cloth.
- Wet the cloth or pad with a small amount of Marine Stainless 2 in 1 and polish onto the surface.
- For heavily stained surfaces, vigorous hand polishing will not damage the surface.
- Evenly treat small areas at a time.
- Once complete, a white film will then appear. (Fig. 2).
- Remove residue with a wet cloth or rinse off thoroughly with fresh water.
- The stainless steel surface should have a polished appearance when complete. (Fig. 3).
- Repeat the application process if tea-staining is still present in certain areas.

3. CURING:

Marine Stainless 2 in 1 is water/corrosion resistant almost immediately after application, reaching optimum protective effect within 12 hours.

4. MAINTENANCE:

- Wipe the surface occasionally with a clean wet cloth or rinse with fresh water.
- Marine Stainless 2 in 1 can be easily re-applied by following the initial application steps.



Fig. 1: Original surface



Fig. 2: White film



Fig. 3: Cleaned & protected surface

International Trading & Consulting Pty Ltd

Unit 4 Platinum Business Park • 34-36 Ralph St • Alexandria • NSW • 2015 • Australia
Ph: +61 2 9669 3555 • Email: info@intc.com.au • www.nanocoat.com.au